

CERTIFICATE FI/41583/A1

Our Ref. HEL-CERT221202034-02



Product Conduit for electrical installations

Type 1) ICTA* 16, ICTA* 20, ICTA* 25, ICTA* 32, ICTA* 40, ICTA* 50
2) ICTAQ* 16, ICTAQ* 20, ICTAQ* 25

Trademark 1) **Pmflex**, PROFIFLEX

2) **Pmflex**

Certificate Holder PM FLEX S.R.L.
Via XXV aprile 15, 24030, Almenno SB (BG), Italy

Technical information See page 2

Other information -

The product is certified according to the following standard(s) EN 61386-1:2008 + A1:2019
EN IEC 61386-22:2021 + A11:2021

Validity This certificate is valid until 2028-01-02 provided that the Conditions for FI certification are met. This certificate includes the right to use the FI mark under the condition that changes (if any) will be checked at SGS Fimko before the product is brought onto market and that the conditions for FI certification are met.

Date of issue 2023-01-13

SGS Fimko Ltd

Signature


Joonas Leinonen
Certification Manager



Manufacturer

PM FLEX S.R.L.
Via XXV aprile 15, 24030, Almenno SB (BG), Italy

Manufacturing site

Same as the manufacturer

Additional information

The products have certificate no. SE-S-2201479R1 issued by Intertek Semko AB in accordance with the Nordic Certification Service system.

This certificate replaces previous certificate FI/41583, dated 2023-01-02, due to correction of the standard.

*In model/type reference specifies colour.

Colour codes (*)

None	Grey
A	Blue
N	Black
V	Green
X	Ivory

Product information for ICTA* 16, ICTA* 20, ICTA* 25, ICTA* 32, ICTA* 40, ICTA* 50:

- Classification code: 3422 or 3343.
- Temperature range: -5°C / 90°C (3422) & -25°C / 105°C (3343).
- Grey coloured corrugated insulating conduits with size 16mm, 20mm, 25mm, 32mm, 40mm and 50mm.
- Non-flame propagating conduits. Pliable/self-recovering.
- Halogen free according to EN 50642:2018.
- The conduits comply with requirements to Low smoke test according to EN 61034-2:2005+A1:2013 and IEC 61034-2:2013, edition 3.1.

Product information for ICTAQ* 16, ICTAQ* 20, ICTAQ* 25:

- Classification code: 3422 or 3343.
- Temperature range: -5°C / 90°C (3422) & -25°C / 105°C (3343).
- Grey and black coloured corrugated insulating conduits with size 16mm, 20mm and 25mm, easy flow.
- Non-flame propagating conduits. Pliable/self-recovering.

As shown in the Test Report(s) No(s): 2200995STO-001, 2200995STO-002